

## Underdeck Air Compressors for **MINE SERVICE VEHICLES**



### Features

- German designed Oil injected EUCOMP rotary screw compressor
- On demand air output up to 4.25 m<sup>3</sup>/m (150 CFM)
- Air pressures up to 13 Bar (190 PSI)
- High temperature shut down
- Park brake interlocking
- Point of operation emergency shut down
- Direct coupled bent axis piston motor
- Soft start hydraulic control valve
- #

### Benefits

- Compressor driven by transmission mounted PTO
- Cost effective alternative to trailer mounted compressors
- Low operational noise
- Space saving design as compressor mounts below deck
- Increased mobility as compressor is incorporated on truck rather than on trailer
- Flexible mounting of components allows efficient weight distribution around chassis
- Available options include skid mount or module design to provide easy installation
- Product support – Mega Pacific's National Sales and Distribution network#

## Compressor Specifications

Compressor Model	Capacity (m <sup>3</sup> /m)	Air (Bar)	Hydraulic Flow (l/m)	Hydraulic Pressure (Bar)
EU11	1.13 (40 CFM)	10	75	80
EU11	1.42 (50 CFM)	10	94	80
EU18	1.84 (65 CFM)	10	56	140
EU18	2.55 (90 CFM)	10	75	140
EU30	3.68 (130 CFM)	10	75	205
EU30	4.25 (150 CFM)	10	84	205

