

Gear Pumps

**NOTE: NEVER CONFIRM OPPOSITION PUMP ROTATION BY STAMPING ON PUMP BODY.
ALWAYS CHECK THE PTO OUTPUT SHAFT ROTATION**

POW AUTO	Rot.	Cc/rev	Max. Bar	Mount Type	PZB Code	Rot. (x)	Adapter
CF-9	0 or S	28	210	Unique	3123022x000	1 or 2	205X241
CF-12	0 or S	38	210	Unique	3123036x000	1 or 2	205X241
CF-15	0 or S	47	200	Unique	3123043x000	1 or 2	205X241
CF-18	0 or S	57	175	Unique	3123057x000	1 or 2	205X241
CF-21	0 or S	66	145	Unique	3123065x000	1 or 2	205X241
D-24	0 or S	64	200	Unique	3123065x000	1 or 2	205X241
D-30	0 or S	76	170	Unique	3123075x000	1 or 2	205X241
K-30	0 or S	30	310	Unique	3123036x000	1 or 2	205X241
K-40	0 or S	40	275	Unique	3123036x000	1 or 2	205X241
K-60	0 or S	60	210	Unique	3123057x000	1 or 2	205X241
K-70	0 or S	70	175	Unique	3123065x000	1 or 2	205X241
CHELSEA	Rot.	Cc/rev	Max. Bar	Mount Type	PZB Code	Rot. (x)	Adapter
P16-85	A or C	27	207	Unique	3123022x000	1 or 2	205X317
P16-100	A or C	32	207	Unique	3123036x000	1 or 2	205X317
P16-115	A or C	36	207	Unique	3123036x000	1 or 2	205X317
P16-150	A or C	48	207	Unique	3123043x000	1 or 2	205X317
P16-180	A or C	57	152	Unique	3123057x000	1 or 2	205X317
P16-200	A or C	64	138	Unique	3123065x000	1 or 2	205X317
HP16-85	A or C	27	250	Unique	3123022x000	1 or 2	205X317
HP16-100	A or C	32	250	Unique	3123036x000	1 or 2	205X317
HP16-115	A or C	36	250	Unique	3123036x000	1 or 2	205X317
HP16-150	A or C	48	250	Unique	3123043x000	1 or 2	205X317
HP16-180	A or C	57	220	Unique	3123057x000	1 or 2	205X317
HP16-200	A or C	64	200	Unique	3123065x000	1 or 2	205X317
HP16-250	A or C	80	175	Unique	3123075x000	1 or 2	205X317
OMFB	Rot.	Cc/rev	Max. Bar	Mount Type	PZB Code	Rot. (x)	Adapter
LTA16	S or D	16	220	3Bolt	3123015x000	1 or 2	Not required
LTA20	S or D	20	220	3Bolt	3123022x000	1 or 2	Not required
LTA25	S or D	25	220	3Bolt	3123022x000	1 or 2	Not required
LTA32	S or D	32	200	3Bolt	3123036x000	1 or 2	Not required
LTA40	S or D	40	170	3Bolt	3123043x000	1 or 2	Not required
NPH-17	S or D	17	315	3Bolt OR 4Bolt ISO	3123015x000	1 or 2	***
NPH-22	S or D	22	315	3Bolt OR 4Bolt ISO	3123022x000	1 or 2	***
NPH-27	S or D	27	315	3Bolt OR 4Bolt ISO	3123022x000	1 or 2	***
NPH-34	S or D	34	300	3Bolt OR 4Bolt ISO	3123036x000	1 or 2	***
NPH-43	S or D	43	290	3Bolt OR 4Bolt ISO	3123043x000	1 or 2	***
NPH-51	S or D	51	260	3Bolt OR 4Bolt ISO	3123057x000	1 or 2	***
NPH-61	S or D	61	240	3Bolt OR 4Bolt ISO	3123065x000	1 or 2	***
NPH-73	S or D	73	220	3Bolt OR 4Bolt ISO	3123075x000	1 or 2	***
NPH-82	S or D	82	210	3Bolt OR 4Bolt ISO	3123083x000	1 or 2	***
NPH-100	S or D	100	200	3Bolt OR 4Bolt ISO	3123102x000	1 or 2	***

*** - Check ALL - OMFB pumps have a FULL product code to codify; Rotation, Port rear/side and 3 Bolt or ISO.
***** - CHECK ALL PUMP FOR PORT SIZE AND FITTING ORIENTATION IF REPLACING**

Piston Pumps - Bent Axis

**NOTE: NEVER CONFIRM OPPOSITION PUMP ROTATION BY STAMPING ON PUMP BODY.
ALWAYS CHECK THE PTO OUTPUT SHAFT ROTATION**

OMFB Sunfab	Rot.	Cc/rev	Max. Bar	Mount Type	Leduc Code	Rot.	Adapter
SC-017-L/R	L or R	17	400	ISO 4 Bolt Male	See Tech Dept	1 or 2	None
SC-025-L/R	L or R	25	400	ISO 4 Bolt Male	See Tech Dept	1 or 2	None
SC-034-L/R	L or R	34	400	ISO 4 Bolt Male	XP41-0517650 [#]	#1 or 2	None
SC-047-L/R	L or R	47	400	ISO 4 Bolt Male	XP50-0517625 [#]	#1 or 2	None
SC-056-L/R	L or R	56	400	ISO 4 Bolt Male	XP50-0517625 [#]	#1 or 2	None
SC-064-L/R	L or R	64	400	ISO 4 Bolt Male	XP63-0517635 [#]	#1 or 2	None
SC-084-L/R	L or R	84	400	ISO 4 Bolt Male	XP80-0517610 [#]	#1 or 2	None
SC-108-L/R	L or R	108	400	ISO 4 Bolt Male	XP108-0517620 [#]	#1 or 2	None
Parker F1 (25-61cc)	Rot.	Cc/rev	Max. Bar	Mount Type	Leduc Code	Rot.	Adapter
3781024 / 025	L or R	25	350	ISO 4 Bolt Male	See Tech Dept	1 or 2	None
3781040 / 041	L or R	41	350	ISO 4 Bolt Male	XP41-0517650 [#]	#1 or 2	None
3781050 / 051	L or R	51	350	ISO 4 Bolt Male	XP50-0517625 [#]	#1 or 2	None
3781060 / 061	L or R	61	350	ISO 4 Bolt Male	XP63-0517635 [#]	#1 or 2	None
3781080 / 081	L or R	81	350	ISO 4 Bolt Male	XP80-0517610 [#]	#1 or 2	None
3781100 / 101	L or R	101	350	ISO 4 Bolt Male	XP108-0517620 [#]	#1 or 2	None
* Check that the PTO is bearing support and sealed—otherwise see the Technical Department							
Powauto	Rot.	Cc/rev	Max. Bar	Mount Type	Leduc Code	Rot.	Adapter
PUP ⁻ -30R	~O or S	30	350	Unique	*PAI25-0520150	Bi-Rot	205X241
PUP ⁻ -30R01	~O or S	30	350	ISO 4 Bolt Male	XP41-0517650 [#]	#1 or 2	None
PUP ⁻ -40R	~O or S	40	350	Unique	*PAI40-0520160	Bi-Rot	205X241
PUP ⁻ -40R01	~O or S	40	350	ISO 4 Bolt Male	XP41-0517650 [#]	#1 or 2	None
PUP ⁻ -50R	~O or S	50	350	Unique	*PAI50-0520170	Bi-Rot	205X241
PUP ⁻ -50R01	~O or S	50	350	ISO 4 Bolt Male	XP50-0517625 [#]	#1 or 2	None
PUP ⁻ -63R	~O or S	63	350	Unique	*PAI60-0520180	Bi-Rot	205X241
PUP ⁻ -63R01	~O or S	63	350	ISO 4 Bolt Male	XP63-0517635 [#]	#1 or 2	None
PUP ⁻ -81R01	~O or S	81	350	ISO 4 Bolt Male	XP80-0517610 [#]	#1 or 2	None
PUP ⁻ -108R01	~O or S	108	350	ISO 4 Bolt Male	XP108-0517620 [#]	#1 or 2	None
* Check the maximum speed requirement of the pump including the PTO ratio before specifying							
HYVA	Rot.	Cc/rev	Max. Bar	Mount Type	Leduc Code	Rot.	Adapter
14564 600/605	L or R	40	380	ISO 4 Bolt Male	XP41-0517650 [#]	#1 or 2	None
14564 610/615	L or R	50	380	ISO 4 Bolt Male	XP50-0517625 [#]	#1 or 2	None
14564 620/625	L or R	63	380	ISO 4 Bolt Male	XP63-0517635 [#]	#1 or 2	None
14564 630/635	L or R	80	335	ISO 4 Bolt Male	XP80-0517610 [#]	#1 or 2	None
14564 640/645	L or R	80	380	ISO 4 Bolt Male	XP80-0517610 [#]	#1 or 2	None
*** - CHECK ALL PUMP FOR PORT SIZE AND FITTING ORIENTATION IF REPLACING							